



技术参数:

- 插芯:
- 插针数: 1
 - 额定电流:
 - 不带适配器: 350A
 - 带适配器: 350A
 - 额定电压:
 - 不带适配器: 2000V
 - 带适配器: 4000V
 - 额定脉冲电压:
 - 不带适配器: 12kV
 - 带适配器: 18kV
 - 污染等级: 3
 - 绝缘阻抗: $> 10^{10}\Omega$
 - 材料: 聚酰胺
 - 颜色: RAL 9002 (灰白色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: ≥ 500
- 插针:
- 接线方式: 冷压连接
 - 材料: 铜合金
 - 表面处理: 镀银
 - 接触电阻: $\leq 0.3\text{m}\Omega$
 - 线径范围: 35-120mm²
 - 最大电缆直径: 22mm
 - 冷压模具: 按照 DIN 46 235
 - 压力要求: 130kN
- 固定框架:
- 材料: 不锈钢
 - 外壳固定螺丝的拧紧力矩: 0.5N·m
 - 框架固定螺丝的拧紧力矩: 1.5N·m
- 工具:
- 液压钳: TL05
 - 六角适配器, 适用于350的外壳:
 WNSC-M25M25/APT
 WNSC-M32M32/APT

Technical specification:

- Inserters:
- No. of contact: 1
 - Rated current:
 - Without adapter: 350A
 - With adapter: 350A
 - Rated voltage:
 - Without adapter: 2000V
 - With adapter: 4000V
 - Rated impulse voltage:
 - Without adapter: 12kV
 - With adapter: 18kV
 - Pollution degree: 3
 - Insulation resistance: $> 10^{10}\Omega$
 - Material: polyamide
 - Colour: RAL 9002(light white)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: ≥ 500
- Contacts:
- Terminal: crimp terminal
 - Material: copper alloy
 - Surface: hard-silver plated
 - Contact resistance: $\leq 0.3\text{m}\Omega$
 - Wire gauge: 35-120mm²
 - Max. cable diameter: 22mm
 - Crimp dies: acc. to DIN 46 235
 - Pressing force requirement: 130kN
- Frame:
- Material: stainless steel
 - Tightening torque of the fixing screws: 0.5N·m
 - Tightening torque of the cross-tying: 1.5N·m
- Tools:
- Manual hydraulic clamp: TL05
 - Hexagonal adapter, for 350 Hoods/Housings:
 WNSC-M25M25/APT
 WNSC-M32M32/APT

						表面处理 Finish		-		图号 Drawing No.		-	
						材料 Material		-		产品代号 Part Code		HC350-MC	
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale		版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.	
绘图 Drawn	BQ LUO	姓名/Name	日期/Date	姓名/Name	日期/Date	2:3	V1.2	33.6g	-	1310010100101			
审核 Checked	HZ LAN	日期/Date	14.03.2019	姓名/Name	日期/Date					产品名称 Part Name			
工艺 Process	-	日期/Date	-	姓名/Name	日期/Date					-			
		批准 Approved	HQ ZHANG	日期/Date	14.03.2019	All Dimensions in mm Original Size DIN A 4		厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.,LTD					