

技术参数:

插芯:

- 插针数: 108
- 额定电流: 7.5A
- 额定电压: 200V
- 额定脉冲电压: 4kV
- 污染等级: 3
- 污染等级为2时的参数: 7.5A 320V 4kV 2
- 污染等级为1时的参数: 7.5A 1000V 4kV 1
- 绝缘阻抗:  $> 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数:  $> 500$




插针:

- 接线方式: 焊接连接
- 材料: 铜合金
- 表面处理:
  - 接触端镀银
  - 焊接端镀锡
- 接触电阻:  $\leq 15\text{m}\Omega$
- PIN针间距:  $4.5^{\circ}\times 4.5\text{mm}$

Technical specification:

Inserts:

- No. of contact: 108
  - Rated current: 7.5A
  - Rated voltage: 200V
  - Rated impulse voltage: 4kV
  - Pollution degree: 3
  - Pollution degree 2: 7.5A 320V 4kV 2
  - Pollution degree 1: 7.5A 1000V 4kV 1
  - Insulation resistance:  $> 10^{10}\Omega$
  - Material: polycarbonate
  - Colour: RAL 7032(light grey)
  - Temperature range:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
  - Flammability acc.to UL 94: V0
  - Mating cycles:  $> 500$
- Contacts:
- Terminal: soldering
  - Material: copper alloy
  - Surface:
    - Contact silver plated
    - terminal tin plated
  - Contact resistance:  $\leq 15\text{m}\Omega$
  - PIN needle spacing:  $4.5^{\circ}\times 4.5\text{mm}$

|               |              |                  |                |          |                 |   |            |   |            |   |                  |               |
|---------------|--------------|------------------|----------------|----------|-----------------|---|------------|---|------------|---|------------------|---------------|
|               |              |                  |                |          |                 | 表面处理<br>Finish  | -          |   |            | 图号<br>Drawing No.   | -                |               |
|               |              |                  |                |          |                 | 材料<br>Material  | -          |   |            | 产品代号<br>Part Code   | HDD-108-MSHT     |               |
| 标记<br>Mark    | 处数<br>Number | 变更描述/Description |                |          | 签名<br>Signature |   | 日期<br>Date |   |            |   | 产品料号<br>Part No. | 1261080131001 |
|               | 姓名/Name      | 日期/Date          |                | 姓名/Name  | 日期/Date         | 比例<br>Scale   | 版本<br>REV. | 重量<br>Weight                                  | 数量<br>Qty. | 产品名称<br>Part Name   | -                |               |
| 绘图<br>Drawn   | HZ LAN       | 21.05.2018       | 标准化<br>Stand.  | -        | -               | 2:3   | V1.0       | -g  | -          |   |                  |               |
| 审核<br>Checked | HQ ZHANG     | 21.05.2018       |                |          |                 |   |            |   |            |   |                  |               |
| 工艺<br>Process | -            | -                | 批准<br>Approved | HQ ZHANG | 21.05.2018      |   |            | All Dimensions in mm<br>Original Size DIN A 4 |            |  厦门唯恩电气有限公司<br>XIAMEN WAIN ELECTRICAL CO.LTD |                  |               |